



**RADIO FREQUENCY
INDUSTRIES (PTY.) LTD.**

"Simply The Best"

CK No : 2005/006095/07 Phone : +27(0) 11 869 9285
 VAT No : 4470219918 Fax : +27(0) 86 509 2874
 rf-sales@rfind.co.za Cell : +27(0) 82 765 3007

24 Hendrik Potgieter Street, P.O. Box 1500
 Corner 5th Avenue ALBERTON
 ALBERTON NORTH, 1450 1450

RF - LIGHTNING PROTECTORS



<u>SPECIFICATIONS:</u>	<u>LIPRO-N</u>	<u>LIPRO-U</u>
Power :	100Watts	100Watts
Frequency Range :	1-1250MHz.	1-1000MHz.
Impedance :	50 Ohm	50 Ohm
Size :	70 X 38 X 25 mm	70 X 38 X 25 mm
Connectors :	N-Female To N-Female	UHF Female To UHF Female
Impulse Discharge Current :	20kA	20kA
Dynamic Spark Over Voltage :	950V	950V
Static Spark Over Voltage :	350V	350V
Alternating Discharge Current :	20A	20A
Glow Discharge Voltage :	72V	72V
Isolation :	Capacitive	Capacitive
DC Block :	Block DC Voltage	Block DC Voltage
Mounting :	Bracket Mount	Bracket Mount

Manufacturers of : Two-Way Radio Antennas, Duplexers, Filters, Combiners, Splitters, Lightning protectors & other RF Products.
 Sales and Distribution of: Two-Way Radios, Repeater Systems, Power Meters, Microphones, Power Supplies, Cables & Connectors.